



Cell(电芯):	LP103450	Date code(日期):		Inner controlling standard(内控标准)		
Battery Specification (电池参数)	Min.Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single battery capacity (单体电池容量)	1700	* PCM protection (保护板参数)	Overcurrent Detection(A) (过流值) Only applicable for Max.Discharge current of <u>2</u> A. (仅适用于最大 <u>2</u> A的放电电流)	2-6	
	Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single battery capacity (单体电池容量)	1800		Overcharge Detection Voltage(V) (过充保护电压)	4.28±0.05	
	Nominal Voltage 标称电压 (V)	3.7		Overdischarge Detection Voltage(V) (过放保护电压)	2.3±0.1	
	Internal impedance 内阻(≡) (mΩ, AC 1KHz)	200		Charge Temp. 充电温度 (°C)	0-45	
Ambient Conditions (工作环境)		Discharge Temp. 放电温度 (°C)		-20-60	Humidity(湿度)	65±20%

Remark(备注):
 1. No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. Rohs compliant(严格按照ROHS要求生产).

		Drawn:	Moyongdi	Revise No.:	E4-2009
		Checked 1:	Chris	Projection:	
Title	LP103450-PCM-LD	Checked 2:	Keyan	Page:	1/1
File NO.	A03445	Approved:		Scale:	1 : 1
		Draw Date:	2010/07/08	Unit:	mm